

MIG TORCHES & PARTS

(OCIM® Compatible)



MODEL NOS:

Power at 60%
CO₂ - MIX

TW25-OBx3 280A – 240A
TW40-OBx4 400A – 360A

Length : 3M, 4M or as required

Connections : Euro, Bernard® Hobart®
Tweco® etc as Required

Process: MIG/MAG

Method of Guidance: Manual

Type of Cooling: Air

Diameter Range of Solid Wire: D1.0 – 1.4
and Flux cored Wire: D1.6 – 2.4

CONTACT TIPS / GAS DIFFUSOR / GAS NOZZLE



PART NO

REF

1	CT-EO-30-0.8	M6x30x0.8 (E-Cu)
2	CT-EO-40-1.2 CT-ZO-40-1.2	M8x40x1.2 (E-Cu) M8x40x1.2 (CuCrZr)
9	GD-25-O	TW25 OB / TW25M
10	GD-36-O	TW36 OB / TW36M
11	GD-40-O	TW40 OB / TW40M
12	GN-25-O	TW25 OB / TW25M
13	GN-36-O	TW36 OB / TW36M
14	GN-40-O	TW40 OB / TW40M

SWAN NECK



PART NO

REF

3	SN-25-O	TW25M
4	SN-36-O	TW36M
5	SN-40-O	TW40M
6	SN-25-OB	TW25 OB
7	SN-36-OB	TW36 OB
8	SN-40-OB	TW40 OB

Parts & Torches offered by Truweld Welding Industries are not genuine parts & are only compatible parts.

Reference to Brand, Torch & Part No is only for convenience.

AUTHORISED DISTRIBUTOR

Product of:
**TRUWELD
WELDING
INDUSTRIES**